SHANNON COUNTY

INCLUDED: [Significant feature(s) of bridge given in boldface] [Field inventoried bridge indicated by asterisk]

[Their inventoried bridge indicated by asterisk]								
Inv. No.	MHTD	Bridge Name	e	Descript	tion			
*SHAN01	G 804A	Current Rive	er Bridge	5-130'	concrete filled spandrel arch			
*SHAN02	H 79	Sinking Creek Bridge Round Spring Bridge		1924 3- 80'	M.E. Gillioz, Monett, MO concrete open spandrel arch Public Works Construction Co. concrete open spandrel arch			
*SHAN03	J 420			1925 1-150'				
*SHAN04	K 209	Eminence Br	idge	1930 3-110' 1933	C.F. Johnson and Son concrete open spandrel arch List & Clark Construction Co.			
EXCLUDED) :							
Steel string J 646	ger K 274	K 924	K 989	T 157	T 789			
Steel pipe R 818	culvert R 819							
Concrete gi	irder							
Concrete sl	ah							

Concrete slab 153001.6 306000.7 306001.7 464000.1

Concrete box culvert J 747 K 273 K 935 K 975 Y 174 037500.1 037500.2 190000.2 190000.5 249001.1 302001.1 302002.2 302002.3 305001.2

SUMMARY:

	Primary	Secondary	Urban	Other	Total
Included Excluded	4 13	0 14	0	0 0	4 27
	17	14	0	0	31 structures

Current River Bridge

SHAN01

GENERAL DATA

structure no.: G 804A county: Shannon

city/town:

0.3 mile north of Round Spring feature inters.: Current River

cadastral grid: S20, T30N, R4W

highway route: Missouri State Highway 19

highway distr.: 9

current owner: Missouri Highway and Transportation Depart-

ment

STRUCTURAL DATA

superstructure: concrete filled spandrel arch

substructure: concrete abutments, wingwalls and piers

span number:

condition:

good

span length:

130.0'

alterations: none

total length: 602.0

floor/decking: concrete deck

roadway width: 18.0'

other features: concrete guardrails (standard Missouri High-

way Department design); bridge plate: Missouri Highway Dept. Bridge N° 804 1924

HISTORICAL DATA

erection date: 1924

erection cost: \$71,471.39

designer:

Missouri State Highway Department

fabricator:

none

contractor:

M.E. Gillioz, Monett MO

references:

Missouri Highway and Transportation Department, Structure Inventory and Appraisal: Structure Number G 804A; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Fourth Biennial Report of the Missouri State Highway Commission (1923-24), p. 170; field inspection by Carl

McWilliams and Richard Collier, 29 March 1992.

sign. rating:

evaluation:

NRHP possibly eligible

inventoried by: Carl McWilliams 6 May 1992

Sinking Creek Bridge

SHAN02

GENERAL DATA

structure no.: H 79

city/town:

0.6 mile north of Round Spring

county:

Shannon

feature Inters.: Sinking Creek

cadastral grid: S17/18, T30N, R4W

highway route: Missouri State Highway 19

highway distr.: 9

current owner: Missouri Highway and Transportation Depart-

ment

STRUCTURAL DATA

superstructure: concrete, 2-rib, open spandrel arch; 1 concrete deck girder approach

span at each end

concrete abutments, wingwalls and piers substructure:

span number:

condition:

good

80.0 span length:

alterations:

none

total length: 339.0' floor/decking: concrete deck

roadway width: 18.0'

other features: concrete guardrails (standard Missouri State Highway Department design); bridge plate:

Missouri Highway Dept. Bridge Nº H 79 1925

HISTORICAL DATA

erection date: 1925

erection cost: \$38,724.07

designer:

Missouri State Highway Department

fabricator:

contractor:

Public Works Construction Company

references:

Missouri Highway and Transportation Department, Structure Inventory and Appraisal: Structure Number H 79; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Fifth Biennial Report of the Missouri State Highway Commission (1925-26), p. 217; field inspection by Richard

Collier and Carl McWilliams, 29 March 1992.

sign. rating:

50

evaluation:

NRHP possibly eligible

inventoried by: Carl McWilliams

6 May 1992

Round Spring Bridge

SHAN03

GENERAL DATA

structure no.: J 420 county:

Shannon

city/town:

Round Spring

feature inters.: Spring Valley Creek cadastral grid: S19/20, T30N, R4W

highway route: Missouri State Highway 19

highway distr.: 9

current owner: Missouri Highway and Transportation Depart-

ment

STRUCTURAL DATA

superstructure: concrete, 2-rib, open spandrel arch; 3 concrete deck girder approach

spans at the north end; 4 concrete deck girder approach spans at the

south end

concrete abutments, wingwalls and piers substructure:

span number:

condition:

good

span length:

150.0'

alterations:

none

523.0' total length: roadway width: 20.0'

floor/decking: concrete deck

other features: concrete guardrails (standard Missouri State

Highway Department design); bridge plate: Missouri Highway Department Bridge No J-

420 1930

HISTORICAL DATA

erection date: 1930

erection cost: \$70,152.85

designer:

Missouri State Highway Department

fabricator:

none

contractor:

C.F. Johnson and Son

references:

Missouri Highway and Transportation Department, Structure Inventory and Appraisal: Štructure Number J 420; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Seventh Biennial Report of the Missouri State Highway Commission (1929-30), p. 261; field inspection by

Carl McWilliams and Richard Collier, 29 March 1992.

sign. rating:

evaluation:

NRHP possibly eligible

inventoried by: Carl McWilliams 6 May 1992

Eminence Bridge

SHAN04

GENERAL DATA

structure no.: K 209 county:

Eminence city/town:

Shannon

feature inters.: Jacks Fork of Current River

cadastral grid: S26, T29N, R4W

highway route: Missouri State Highway 19

highway distr.: 9

current owner: Missouri Highway and Transportation Depart-

STRUCTURAL DATA

superstructure: concrete, 2-rib, open spandrel arch; 2 concrete deck girder approach

spans at the north end; 1 concrete deck girder approach span at the

south end

concrete abutments, wingwalls and piers substructure:

3 span number: span length: 110.0'

condition:

good

total length: 430.0 alterations: none

roadway width: 22.0'

floor/decking: concrete deck

other features: concrete guardrails (standard Missouri State Highway Department design); bridge plate:

Missouri Highway Dept. Bridge K 209 1933

HISTORICAL DATA

erection date: 1933

erection cost: \$50,514.75

designer:

Missouri State Highway Department

fabricator:

List and Clark Construction Company contractor:

Missouri Highway and Transportation Department, Structure Inventory references:

and Appraisal: Structure Number K 209; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Ninth Biennial Report of the Missouri State Highway Commission (1933-34), pp. 186-87; field inspection by

Carl McWilliams and Richard Collier, 29 March 1992.

sign. rating:

NRHP possibly eligible evaluation:

inventoried by: Carl McWilliams 6 May 1992



Current River Bridge

MHTD: G 804A

LOCATION

Missouri State Highway 19 over Current River; S20, T30N, R4W

0.3 mile north of Round Spring; Shannon County, Missouri

DATE(S) OF CONSTRUCTION SHAN01

1924

USE (ORIGINAL / CURRENT)

highway bridge / highway bridge

RATING NRHP possibly eligible (score: 57)

CONDITION **OWNER**

Missouri Highway and Transportation Department good

span number: 5 superstructure: concrete filled spandrel arch

span length: 130.0' substructure: concrete abutments, wingwalls and piers

total length: 602.0 floor/decking: concrete deck

roadway wdt.: 18.0' other features: concrete guardrails (standard Missouri Highway Department design); bridge plate:


Missouri Highway Dept. Bridge N° 804 1924

Extending through southern Missouri's scenic Ozarks, State Highway 19 is Shannon County's principal north-south highway. In the early 1920s, the Missouri State Highway Commission began efforts to modernize the roadway, including the replacement of bridges over the route's larger waterways. Opting for concrete construction rather than steel, the highway commission built a series of graceful arches, that blended nicely with the mountainous terrain. Comprised of three, 130-foot open spandrel arches, flanked on either end by 60-foot filled spandrel arches, this bridge was erected where the Current River intersected the highway just north of Round Spring. Drawings were prepared in the fall of 1923, and by year's end the project had been put out to bid. On January 29, 1924, a contract for the bridge's construction was awarded to M.E. Gillioz. Based in Monett, Missouri, Gillioz was one of southern Missouri's more prolific builders during the 1920s and 1930s. Comprised of three 130-foot arches, and two 60-foot arches, Gillioz completed the crossing later that year. Unchanged from its original construction, the Current River Bridge displays a high degree of historical integrity as it continues to carry traffic in the Missouri Ozarks.

The Missouri State Highway Department characteristically used filled spandrel designs for its concrete arches with 80 feet or less of span; open spandrel arches were employed for longer-span applications. MSHD engineers designed numerous single-span examples of the former configuration in the 1920s and 1930s, but few filled spandrel arches with multiple spans. A handful of these large-scale bridges have been identified by the statewide bridge inventory. The Current River Bridge's 130-foot span ranks as Missouri's longest-span filled spandrel arch. Moreover, the structure's five spans is unsurpassed among the state's other filled spandrel arches. The Current River Bridge thus is distinguished as a technologically significant representative of Missouri State Highway Department concrete design of the 1920s.

Current River Bridge

PHOTOS AND SKETCH MAP OF LOCATION







LOCATION MAP

TAKEN FROM MISSOURI HIGHWAY AND TRANSPORTATION DEPARTMENT
GENERAL HIGHWAY MAP

SOURCES

Missouri Highway and Transportation Department, Structure Inventory and Appraisal: Structure Number G 804A; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Fourth Biennial Report of the Missouri State Highway Commission (1923-24), p. 170; field inspection by Carl McWilliams and Richard Collier, 29 March 1992.



SHAN02

NAME(S) OF STRUCTURE

Sinking Creek Bridge

MHTD: H 79

LOCATION

Missouri State Highway 19 over Sinking Creek; S17/18, T30N, R4W

0.6 mile north of Round Spring; Shannon County, Missouri

DATE(S) OF CONSTRUCTION

1925

USE (ORIGINAL / CURRENT)

highway bridge / highway bridge

RATING NRHP possibly eligible (score: 50)


сонопіон оwner good Missouri F			ghway and Transportation Department		
-	span number: 3 span length: 80.0' total length: 339.0' roadway wdt.: 18.0'	superstructure: substructure: floor/decking: other features:	concrete abutments, wingwalls and piers concrete deck		

Extending through southern Missouri's scenic Ozarks, State Highway 19 is Shannon County's principal north-south highway. In the early 1920s, the Missouri State Highway Commission began efforts to modernize the roadway, including the replacement of bridges over the route's larger waterways. Opting for concrete construction, rather than steel, the Highway Commission built a series of graceful open-spandrel arches, that blended nicely with the mountainous terrain. Among the first such bridges was this three-span arch, erected over Sinking Creek, where it intersected the highway about ½ mile north of Round Spring. Design work was prepared by the Highway Commission in early 1925. Bids were solicited that spring, and on June 26th, a \$38,724.07 contract for the bridge's construction was awarded to the Public Works Construction Company. Comprised of three 80-foot open-spandrel arches, the structure was flanked on each end by 40-foot concrete deck girder approaches. The crossing was completed in the fall of 1925, as planned and on schedule. Still in use, the Sinking Creek Bridge is unchanged from its original construction. As such, the crossing possesses a high degree of historical integrity.

The Missouri State Highway Department typically used open spandrel designs for its concrete arches with 80 feet or more of span; with some exceptions, filled spandrel arches were employed for shorter-span applications. MSHD engineers designed a number of open spandrel arches in the 1920s and '30s, employing both single and multiple span configurations. Among those identified by the statewide bridge inventory, the Sinking Creek Bridge rates as a well-preserved, representative example of open spandrel arch construction.

Sinking Creek Bridge

PHOTOS AND SKETCH MAP OF LOCATION



LOCATION MAP

TAKEN FROM MISSOURI HIGHWAY AND TRANSPORTATION DEPARTMENT
GENERAL HIGHWAY MAP





SOURCES

Missouri Highway and Transportation Department, Structure Inventory and Appraisal: Structure Number H 79; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Fifth Biennial Report of the Missouri State Highway Commission (1925-26), p. 217; field inspection by Richard Collier and Carl McWilliams, 29 March 1992.



Round Spring Bridge (Spring Valley Bridge)

SHAN03

DATE(S) OF CONSTRUCTION

1930

MHTD: J 420

Missouri State Highway 19 over Spring Valley Creek; S19/20, T30N, R4W

other features:

Round Spring: Shannon County, Missouri

USE (ORIGINAL / CURRENT)

highway bridge / highway bridge

RATING NRHP potentially eligible (score: 53)

condition
good

Missouri Highway and Transportation Department

span number: 1 superstructure: concrete, 2-rib, open spandrel arch; 3 concrete deck girder approach spans at the north end; 4 concrete deck girder approach spans at the south end total length: 523.0' substructure: concrete abutments, wingwalls and piers roadway wdt.: 20.0' floor/decking: concrete deck

concrete guardrails (standard Missouri State Highway Department design); bridge plate:


Missouri Highway Department Bridge Nº J-420 1930

Extending through southern Missouri's scenic Ozarks, State Highway 19 is Shannon County's principal north-south highway. In the early 1920s, the Missouri State Highway Commission began efforts to modernize the roadway, including the replacement of bridges over the route's larger waterways. Opting for concrete construction, rather than steel, the Highway Commission built a series of graceful open-spandrel arches, that blended nicely with the mountainous terrain. Perhaps the most impressive of these bridges was this skewed, open-spandrel arch, erected over Spring Valley Creek, along one of the highway's most picturesque stretches. Located within the Ozark National Scenic Riverways, the bridge is adjacent to a nearly perfectly round spring. Ages ago, the spring was underground - within a natural cave - but the cave's roof has long since collapsed, and the spring is now open, displaying waters with a deep green hue. Drawings for the crossing, which takes its name from the spring, were prepared in early 1930. In the spring of that year, the project was put out to bid. On April 28, 1930, a contract for the bridge's construction was awarded to C.F. Johnson and Sons. Comprised of a single 150-foot arch over Spring Creek's channel, the bridge was flanked by seven concrete deck girder approaches. Johnson and Sons completed the structure later that year for just over \$70,000.00. Located where the highway leads into a sweeping curve, the bridge continues to carry moderate traffic loads. Unchanged from its original construction, the Round Spring Bridge possess a high degree of historical integrity.

The Missouri State Highway Department characteristically used open-spandrel designs for its concrete arches with 80 feet or more of span; with some exceptions, filled-spandrel arches were typically employed for shorter-span applications. MSHD engineers designed a number of open-spandrel arches in the 1920s and '30s, employing both single and multiple span configurations. Among those identified by the statewide bridge inventory, the Round Spring Bridge rates as superlative example of open-spandrel arch construction. Possessing strong integrity of both design and setting, the structure is surpassed in span length only by the Branson Bridge in Taney County (Structure No. J 705 R).


Round Spring Bridge (Spring Valley Bridge)


PHOTOS AND SKETCH MAP OF LOCATION




LOCATION MAP

TAKEN FROM MISSOURI HIGHWAY AND TRANSPORTATION DEPARTMENT
GENERAL HIGHWAY MAP









SOURCES

Missouri Highway and Transportation Department, Structure Inventory and Appraisal: Structure Number J 420; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Seventh Biennial Report of the Missouri State Highway Commission (1929-30), p. 261; field inspection by Carl McWilliams and Richard Collier, 29 March 1992.



Eminence Bridge (Jacks Fork Bridge)

SHAN04

DATE(S) OF CONSTRUCTION

1933

MHTD: K 209

LOCATION

Missouri State Highway 19 over Jacks Fork of Current River; S26, T29N, R4W

Eminence; Shannon County County, Missouri

USE (ORIGINAL / CURRENT)

highway bridge / highway bridge

RATING NRHP potentially eligible (score: 50)

CONDITION good	OWNER Missouri Highway and Transportation Department			
span number: 3 span length: 110.0' total length: 430.0'	superstructure: concrete, 2-rib, open spandrel arch; 2 concrete deck girder approach spans at the nend; 1 concrete deck girder approach span at the south end concrete abutments, wingwalls and piers	orth		
roadway wdt.: 22.0'	floor/decking: concrete deck other features: concrete guardrails (standard Missouri State Highway Department design); bridge p	late:		

Extending through southern Missouri's scenic Ozarks, State Highway 19 is Shannon County's principal north-south highway. In the early 1920s, the Missouri State Highway Commission began efforts to modernize the roadway, including the replacement of bridges over the route's larger waterways. Opting for concrete construction, rather than steel, the Highway Commission built a series of graceful open-spandrel arches, that blended nicely with the mountainous terrain. Erected late in the series was this three-span open spandrel arch, erected over the Jack's Fork of the Current River, at the north edge of Eminence. Drawings were prepared in early fall 1933. Following


Missouri Highway Dept. Bridge K 209 1933

a bidding process, on October 28th, the List and Clark Construction Company was awarded a \$50,514.75 contract for the bridge's construction. Embracing three 110-foot arches, and three 25-foot concrete deck girder approaches, the crossing was completed early the following year. Unchanged from its original construction, the Eminence Bridge displays strong attributes of historical integrity. Continuing to carry traffic, the bridge remains an integral part of State Highway 19.

The Missouri State Highway Department characteristically used open-spandrel designs for its concrete arches with 80 feet or more of span; with some exceptions, filled-spandrel arches were typically employed for shorter-span applications. MSHD engineers designed a number of open-spandrel arches in the 1920s and '30s, employing both single and multiple span configurations. Among those identified by the statewide bridge inventory, the Eminence Bridge is a well-preserved, representative example of open spandrel arch construction.

Eminence Bridge (Jacks Fork Bridge)

PHOTOS AND SKETCH MAP OF LOCATION









LOCATION MAP

TAKEN FROM MISSOURI HIGHWAY AND TRANSPORTATION DEPARTMENT GENERAL HIGHWAY MAP

SOURCES

Missouri Highway and Transportation Department, Structure Inventory and Appraisal: Structure Number K 209; Missouri Primary System Bridge Record, located at the Missouri Highway and Transportation Department, Jefferson City MO; Ninth Biennial Report of the Missouri State Highway Commission (1933-34), pp. 186-87; field inspection by Carl McWilliams and Richard Collier, 29 March 1992.

INVENTORIED BYCarl McWilliams

AFFILIATIONFraserdesign, Loveland CO

DATE 6 May 1992